


Fast, economical repair for damaged fiber drop cables

Features

- Robust, weatherproof thermoplastic housing
- Housing supports fusion splicing (2) and connector bulkhead
- Fast repair kit for where fiber slack is not available –identifiable with programed OTDR
- Direct bury, strand, wall or pole mounting
- Tone wire connection point for underground locating



LOC-DROP® Housing

Applications


Service providers are committed to quickly and effectively connecting new customers and addressing service outages.

The LOC-DROP® multi-use enclosure is the ultimate cost-effective alternative to larger termination boxes when only a couple of termination points are needed.


Modern subscribers are increasingly intolerant of extended service outages. The LOC-DROP® multi-use enclosure also stands as the cost-saving option for replacing a subscriber's severed fiber drop cable helping to eliminate the need for a second truck role.

Furthermore, the LOC-DROP® Fast Repair kit comprises a complete assembly of two housings interconnected with SC/APC-terminated micro-armored cable, ensuring rapid restoration times.

LOC-DROP® represents the most robust and permanent installation and repair solution for aerial or buried deployments with both traditional fiber and microduct solutions.






LOC-DROP® Fast Repair Kit



Shown with Strand Mount Brackets





Specifications

	UoM	LOC-DROP® Housing	LOC-DROP® Fast Repair Kit
Capacity		<ul style="list-style-type: none"> Up to 2 single fusion splices Accepts one bulkhead adapter 	<ul style="list-style-type: none"> Up to 2 single fusion splices One bulkhead adapter
Dimensions	in	8.75 x 3.75 x 2.25	8.75 x 3.75 x 2.25 (x2)
Weight	lbs.	0.6	2.1

Ordering Information

Part Number	Description
KN-LOCDROP-EN	LOC-DROP® housing, includes two large hole entry port nuts and two oval hole grommets for flat drop cables, two small hole entry port nuts and two round hole grommets for Fast Access-type drop cables, one SC (green) bulkhead adapter
KN-LOCDROP-2SCAPC	LOC-DROP® Fast Repair Kit, two LOC-DROP® housings incl. SC/APC-SC/APC pre-installed 51.5' micro-armored cable assembly with tracer wire, two SC simplex adapters, 2 sets of entry ports nuts and grommets for flat drop or quick access drop cables
KN-LOCDROP-SM-10	Strand mount brackets, 10 pairs, with strain relief boots and hardware, for 10 LOC-DROP® housings
KN-LD-RNGK2-20	Replacement nut/grommet kits, each kit contains 2 sets of oval grommets/large hole nuts, 2 sets round hole grommets/small hole nuts, 20 kits

This specification is intended as a guide only. Whilst the information it contains is believed to be correct, KNET can take no responsibility for action taken based on the information contained in this document. KNET reserved the right to make changes to this document without notice. All sales of product are subject to KNET's terms and conditions of sales only.
Any unauthorized copying of this document or our products is prohibited and KNET will take action to prevent any infringement of it rights and to claim damages for the loss that it suffers.

